

Factory-Verified Replacement

MERYDOM 11-20 0541/1-02123


Certified for interchange with IMO 11-20 0541/1-02123. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL	REFERENCE
11-20 0541/1-02123	IMO 11-20 0541/1-02123
SERIES	STRUCTURE
120 Series	D rt nokta temasl bilyal
OVERALL OD	OVERALL ID
640.8 mm	472 mm
OVERALL HEIGHT	GEAR
mm	D tan di li

Published Technical Drawing



imo-11200541102123-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	11-20 0541/1-02123
Certified interchangeable with	IMO 11-20 0541/1-02123
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	N2TDKJHKHHLZ4A2GVQJLATNKLM
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	IMO
Reference series	120 Series
Reference model	11-20 0541/1-02123
Bearing structure	D rt nokta temasl bilyal
Gear arrangement	D tan di li
DIMENSION	
Overall outside diameter (Da)	640,8 mm
Overall inside diameter (di)	472 mm
MOUNTING	
Outer ring bolt circle (La)	43 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MOUNTING (CONTINUED)	
Outer ring mounting-hole count (na)	585
Common mounting-hole diameter (B)	28 mm
Inner ring bolt circle (Li)	498 mm
Inner ring mounting-hole count (ni)	32
GEAR	
Gear pitch diameter (d)	630 mm
Gear module (m)	6 mm
Gear tooth count (z)	105
PERFORMANCE	
Permitted circumferential force, normal (fz_norm)	17,5 kN
Permitted circumferential force, maximum (fz_max)	32,7 kN
Static radial load rating (Co_rad)	334 kN
Static axial load rating (Co_ax)	780 kN
Dynamic radial load rating (C_rad)	173 kN
Dynamic axial load rating (C_ax)	174 kN
PERFORMANCE RATINGS	
Fz Norm	17,5 kN Not simultaneous with other listed dynamic ratings
Fz Max	32,7 kN Not simultaneous with other listed dynamic ratings
Co Rad	334 kN Not simultaneous with other listed dynamic ratings
Co Ax	780 kN Not simultaneous with other listed dynamic ratings


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE RATINGS (CONTINUED)	
C Rad	173 kN Not simultaneous with other listed dynamic ratings
C Ax	174 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	585 holes - B 28 mm
Inner ring mounting	32 holes - B 28 mm
GEAR INTERFACE	
Pitch system	module
Module reference	6 mm
Number of teeth	105
SOURCE TRACEABILITY	
Source document code	IMO_SINGLE_ROW_BALL_EN
Source file	imo_dkugeldrehverbindungen_einreihig-en.pdf
PDF page	9
Printed page	Not published
Source language	EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	imo-11200541102123-curve.webp SHA-256: 0260cea44a56711e11de91c16ce1fe6ebf2ae9a66b01549c7456878a2c0e7c02
Outline Drawing	imo-11200541102123-drawing.webp SHA-256: cd90951201cc25f94d902bd39f73a0b149bfaa777bae09d714ed2cd82fd30b8c

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



Bearing ring material: C45N
4 Taper type grease nipples on circumference
Mounting holes equally spaced
Raceway system supplied pre-lubricated
Dimensions without tolerances DIN ISO 2768 coarse

Clearance of precision version

Position	Radial Clearance	Axial Clearance
1	max. 0.03	max. 0.03
2	max. 0.03	max. 0.03
3	max. 0.03	max. 0.03
4	max. 0.04	max. 0.04
5	max. 0.04	max. 0.04
6	max. 0.05	max. 0.05
7	max. 0.05	max. 0.05
8	max. 0.06	max. 0.06

imo-11200541102123-curve.webp | SHA-256: 0260cea44a56711e11de91c16ce1fe6ebf2ae9a66b01549c7456878a2c0e7c02

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID N2TDKJHKHHLZ4A2GVQJLATNKLM	SOURCE DOCUMENT IMO_SINGLE_ROW_BALL_EN
SOURCE FILE imo_dkugeldrehverbindungen_einreihig-en.pdf	SOURCE LOCATION PDF page 9 Printed page Not published
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/imo/11-20-0541-1-02123/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.