

Factory-Verified Replacement

MERYDOM 90-32 1255/0-06045

Certified for interchange with IMO 90-32 1255/0-06045.
This document consolidates the public product record,
complete published specifications, technical media,
source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

90-32 1255/0-06045

REFERENCE

IMO 90-32 1255/0-06045

SERIES

932 Series

STRUCTURE

Flan l bilezikli bilyal rulman

OVERALL OD

1,400 mm

OVERALL ID

1,105 mm

OVERALL HEIGHT

mm

GEAR

Di lisiz

Published Technical Drawing



imo-90321255006045-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	90-32 1255/0-06045
Certified interchangeable with	IMO 90-32 1255/0-06045
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	IKUHKTEBYJLRYOBXSNOUYHVVMS
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	IMO
Reference series	932 Series
Reference model	90-32 1255/0-06045
Bearing structure	Flan l bilezikli bilyal rulman
Gear arrangement	Di lisiz
DIMENSION	
Overall outside diameter (Da)	1 400 mm
Overall inside diameter (di)	1 105 mm
Assembly weight (G)	172 kg

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MOUNTING	
Outer ring bolt circle (La)	1 360 mm
Outer ring mounting-hole count (na)	42
Inner ring bolt circle (Li)	1 145 mm
Inner ring mounting-hole count (ni)	42
PERFORMANCE	
Static radial load rating (Co_rad)	1 353 kN
Static axial load rating (Co_ax)	3 619 kN
Dynamic radial load rating (C_rad)	456 kN
Dynamic axial load rating (C_ax)	531 kN
PERFORMANCE RATINGS	
Co Rad	1 353 kN Not simultaneous with other listed dynamic ratings
Co Ax	3 619 kN Not simultaneous with other listed dynamic ratings
C Rad	456 kN Not simultaneous with other listed dynamic ratings
C Ax	531 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	42 holes - See source drawing
Inner ring mounting	42 holes - See source drawing
GEAR INTERFACE	
Integral gear	Not applicable - ungeared bearing
SOURCE TRACEABILITY	


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Source document code	IMO_FLANGE_BALL_EN
Source file	imo_kugeldrehverbindung_mit_flanschring-en.pdf
PDF page	7
Printed page	Not published
Source language	EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	imo-90321255006045-curve.webp SHA-256: a44feff5429d64f7d07f60850d7264707f422d0db41338a7dd379f06d9 b83d9f
Outline Drawing	imo-90321255006045-drawing.webp SHA-256: a7b3ea7414e98cf4e3b3dbefec2ad21c277d1a7289ac0de3d5305f88df 9f914f

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



Radial clearance: 0 - 0.2 mm
Axial tilting clearance: 0 - 0.4 mm
Bearing ring material: C45N
6 Taper type grease nipples on the circumference
Mounting holes equally spaced
Raceway system supplied pre-lubricated.
Dimensions without tolerances DIN ISO 2768 coarse

imo-90321255006045-curve.webp | SHA-256: a44feff5429d64f7d07f60850d7264707f422d0db41338a7dd379f06d9b83d9f

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID IKUHKTEBYJLRYOBXSNOUYHVMS	SOURCE DOCUMENT IMO_FLANGE_BALL_EN
SOURCE FILE imo_kugeldrehverbindung_mit_flanschring-en.pdf	SOURCE LOCATION PDF page 7 Printed page Not published
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/imo/90-32-1255-0-06045/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.