

Factory-Verified Replacement

MERYDOM VSA 200544 N

Certified for interchange with INA VSA 200544 N. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

VSA 200544 N

SERIES

VSA 20 Series

OVERALL OD

640.3 mm

OVERALL HEIGHT

mm

REFERENCE

INA VSA 200544 N

STRUCTURE

D rt nokta teması bilyal


OVERALL ID

472 mm

GEAR

D tan di li

Published Technical Drawing



Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	VSA 200544 N
Certified interchangeable with	INA VSA 200544 N
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	5FYQLQP3ECZN5DAE4MIUVSF7QW
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	INA
Reference series	VSA 20 Series
Reference model	VSA 200544 N
Bearing structure	D rt nokta temasl bilyal
Gear arrangement	D tan di li
DIMENSION	
Mass (Mass)	43 kg
Overall outside diameter (Da)	640,3 mm
Overall inside diameter (di)	472+0,5 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Inside centring diameter (diZT)	474 mm
Catalog diameter Di (Di)	545,5+0,5 mm
Catalog centring diameter DiZT (DiZT)	547 mm
Catalog diameter da (da)	542,5-0,5 mm
MOUNTING	
Outer ring bolt circle (La)	585 mm
Outer ring mounting-hole count (na)	28
Inner ring bolt circle (Li)	498 mm
Inner ring mounting-hole count (ni)	32
GEAR	
Gear pitch diameter (d0)	630 mm
Gear module (m)	6 mm
Gear tooth count (z)	105
PERFORMANCE	
Maximum permissible radial load (Fr perm)	115,6 kN
Normal tooth force (Fznorm)	21,3 kN
Maximum tooth force (Fzmax)	31,5 kN
Basic dynamic axial load rating (Ca)	188 kN
Basic static axial load rating (C0a)	740 kN
Basic dynamic radial load rating (Cr)	123 kN

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE (CONTINUED)	
Basic static radial load rating (C _{0r})	325 kN
PERFORMANCE RATINGS	
Rating Radial Static	325 kN Not simultaneous with other listed dynamic ratings
Rating Axial Static	740 kN Not simultaneous with other listed dynamic ratings
Rating Radial Dynamic	123 kN Not simultaneous with other listed dynamic ratings
Rating Axial Dynamic	188 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Max	31,5 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Normal	21,3 kN Not simultaneous with other listed dynamic ratings
Rating Radial Load Max	115,6 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	28 holes - See source drawing
Inner ring mounting	32 holes - See source drawing
GEAR INTERFACE	
Pitch system	module
Module reference	6 mm
Number of teeth	105
SOURCE TRACEABILITY	
Source document code	INA-SLEWING-RINGS-CATALOGUE-404-2012
Source file	404_de_en_1.pdf
PDF page	60



Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Printed page	58
Source language	EN-DE
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	ina-g04-curve.webp SHA-256: bc90ef6b06bd5b88e28acf15d86874931dcf598e3a9f103ae06adc5032440b56
Outline Drawing	ina-g04-drawing.webp SHA-256: a5869bfa877f8eacaa47abdb5a51f27f3f77bd3957cc427d2ebd639d378a5a2b

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



ina-g04-curve.webp | SHA-256: bc90ef6b06bd5b88e28acf15d86874931dcf598e3a9f103ae06adc5032440b56

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID**5FYQLQP3ECZN5DAE4MIUVSF7QW****SOURCE DOCUMENT****INA-SLEWING-RINGS-CATALOGUE-404-2012****SOURCE FILE****404_de_en_1.pdf****SOURCE LOCATION****PDF page 60 | Printed page 58****VERIFICATION****Level 3 - MERYDOM Engineering
Verified****REVIEWED BY****MERYDOM Engineering Department**

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/ina/vsa-200544-n/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.