

Factory-Verified Replacement

MERYDOM 16382001

Certified for interchange with Kaydon 16382001. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

16382001

REFERENCE

Kaydon 16382001

SERIES

TR Series

STRUCTURE

s ral makaral

OVERALL OD

3,190.748 mm

OVERALL ID

2,700.858 mm

OVERALL HEIGHT

212.852 mm

GEAR

ten di li

No public model drawing is attached to this record. Submit the application and required interface format for final drawing confirmation.

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	16382001
Certified interchangeable with	Kaydon 16382001
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	44BETBHMNCAXRPSHY57WHQ35KR
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Kaydon
Reference series	TR Series
Reference model	16382001
Bearing structure	s ral makaral
Gear arrangement	ten di li
DIMENSION	
Overall outside diameter (Do)	125.620 in Metric reference: yakla k 3 190,7 mm
Overall inside diameter (di)	106.333 in Metric reference: yakla k 2 700,86 mm
Outer ring inner diameter (Di)	115.280 in Metric reference: yakla k 2 928,1 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Inner ring outer diameter (do)	115.630 in Metric reference: yakla k 2 937 mm
Overall height (H)	8.380 in Metric reference: yakla k 212,9 mm
Assembly weight (G)	5800 lb Metric reference: yakla k 2 630,836 kg
MOUNTING	
Outer ring bolt circle (Lo)	122.812 in Metric reference: yakla k 3 119,42 mm
Inner ring bolt circle (Li)	112.250 in Metric reference: yakla k 2 851,2 mm
GEAR	
Gear pitch diameter (D2)	107.333 in Metric reference: yakla k 2 726,26 mm
Diametral pitch (Pd)	1,5
Gear tooth count (z2)	161
PERFORMANCE	
Maximum gear tooth load (Fz)	93140 lbf Metric reference: yakla k 414,31 kN
Moment load rating (Crm)	9275100 ft lbf Metric reference: yakla k 12 575,35 kN m
PERFORMANCE RATINGS	
Moment	9275100.0000000000 ft lbf Metric reference: yakla k 12 575,35 kN m
Gear Tooth	93140.0000000000 lbf Metric reference: yakla k 414,31 kN
MOUNTING INTERFACES	
Outer ring mounting	72 holes - 1.563
Inner ring mounting	72 holes - 1 1/2-6
GEAR INTERFACE	
Pitch system	DP

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

GEAR INTERFACE (CONTINUED)	
Diametral pitch	1.5 DP
Module reference	16.933333 mm
Number of teeth	161
SOURCE TRACEABILITY	
Source document code	KAYDON-CAT390
Source file	Kaydon_Catalog_390.pdf
PDF page	108
Printed page	106
Source language	EN-US
Original unit system	Inch

Source and Verification Traceability

PUBLIC RECORD UID 44BETBHMNCAXRPSHY57WHQ35KR	SOURCE DOCUMENT KAYDON-CAT390
SOURCE FILE Kaydon_Catalog_390.pdf	SOURCE LOCATION PDF page 108 Printed page 106
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/kaydon/16382001/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.