

Factory-Verified Replacement

MERYDOM V25I001

Certified for interchange with La Leonessa V25I001. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

V25I001

SERIES

1RI Series

OVERALL OD

750 mm

OVERALL HEIGHT

82 mm

REFERENCE

La Leonessa V25I001

STRUCTURE

D rt nokta temasl bilyal


OVERALL ID

546 mm

GEAR

ten di li

Published Technical Drawing



la-leonessa-1ri-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	V25I001
Certified interchangeable with	La Leonessa V25I001
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	E2VXRRICDVNIPTXL2JVFJM7HWD
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	La Leonessa
Reference series	1RI Series
Reference model	V25I001
Bearing structure	D rt nokta temasl bilyal
Gear arrangement	ten di li
DIMENSION	
Mass (P)	100 kg
Overall outside diameter (De)	750 mm
Overall inside diameter (Di)	546 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	82 mm
Dim Dr (Dr)	662 mm
MOUNTING	
Outer ring bolt circle (Ie)	720 mm
Outer ring mounting-hole count (ne)	20
Outer ring mounting-hole specification (Me)	M16
Inner ring bolt circle (Ii)	605 mm
Inner ring mounting-hole count (ni)	20
Inner ring mounting-hole specification (Mi)	M16
GEAR	
Gear module (m)	6 mm
Gear tooth count (z)	93
Gear pitch diameter (Dp)	558 mm
Gear Tooth Height (Hd)	70 mm
PERFORMANCE	
Basic static axial load rating (C0a)	2 330 kN
Static tilting moment rating (M0r)	309 kNm
Normal tooth force (Fnom)	35 kN
Maximum tooth force (Fmax)	70 kN
MISCELLANEOUS	

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MISCELLANEOUS (CONTINUED)	
Pattern (Schema)	A
PERFORMANCE RATINGS	
Rating Axial Static	2 330 kN Not simultaneous with other listed dynamic ratings
Rating Tilting Moment Static	309 kNm Not simultaneous with other listed dynamic ratings
Rating Tooth Force Normal	35 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Max	70 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	20 holes - 20; M16
Inner ring mounting	20 holes - 20; M16
GEAR INTERFACE	
Pitch system	module
Module reference	6 mm
Number of teeth	93
SOURCE TRACEABILITY	
Source document code	LA-LEONESSA-INTERNAL-GEAR-CATALOG-2017
Source file	SLEWING-BEARINGS-WITH-INTERNAL-GEAR.pdf
PDF page	4
Printed page	4
Source language	EN
Original unit system	Metric


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	la-leonessa-1ri-static_load_curve.webp SHA-256: 88ec75fa8bed689f66b14f5b91e2b5afb0052df21fcd350ae92760f6f677df55
Outline Drawing	la-leonessa-1ri-drawing.webp SHA-256: 3c0269351f1480df2b4130d7fb5c79552a0896a4f557467d7b138da54c54c490

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



la-leonessa-1ri-static_load_curve.webp | SHA-256:
88ec75fa8bed689f66b14f5b91e2b5afb0052df21fcd350ae92760f6f677df55

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

E2VXRRICDVNIPTXL2JVFJM7HWD

SOURCE FILE

SLEWING-BEARINGS-WITH-INTERNAL-GEAR.pdf

VERIFICATION

**Level 3 - MERYDOM Engineering
Verified**

SOURCE DOCUMENT

LA-LEONESSA-INTERNAL-GEAR-CATALOG-2017

SOURCE LOCATION

PDF page 4 | Printed page 4

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/la-leonessa/v25i001/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.