

Factory-Verified Replacement

MERYDOM VE061B05

Certified for interchange with La Leonessa VE061B05. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

VE061B05

SERIES

2SE Series

OVERALL OD

614.4 mm

OVERALL HEIGHT

98 mm

REFERENCE

La Leonessa VE061B05

STRUCTURE

Internal Bilateral Pulman


OVERALL ID

378 mm


GEAR

D Tandem

Published Technical Drawing



la-leonessa-2se-drawing.webp



Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	VE061B05
Certified interchangeable with	La Leonessa VE061B05
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	VINQQWYSHNSJ36EL2NW65PYG6D
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	La Leonessa
Reference series	2SE Series
Reference model	VE061B05
Bearing structure	ift s ral bilyal rulman
Gear arrangement	D tan di li
DIMENSION	
Mass (P)	98 kg
Overall outside diameter (De)	614,4 mm
Overall inside diameter (Di)	378 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	98 mm
Dim Dr (Dr)	475 mm
MOUNTING	
Outer ring bolt circle (Ie)	540 mm
Outer ring mounting-hole count (ne)	24
Outer ring mounting-hole specification (Me)	M18
Inner ring bolt circle (Ii)	410 mm
Inner ring mounting-hole count (ni)	24
Inner ring mounting-hole specification (Mi)	M18
GEAR	
Gear module (m)	8 mm
Gear tooth count (z)	74
Addendum modification product x^*m (xm)	4 mm
Liebherr catalogue gear dimension k^*m (km)	0,8 mm
Gear pitch diameter (Dp)	600 mm
Gear Tooth Height (Hd)	80 mm
PERFORMANCE	
Basic static axial load rating (C0a)	1 890 kN
Static tilting moment rating (M0r)	276 kNm
Normal tooth force (Fnom)	62 kN

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE (CONTINUED)	
Maximum tooth force (Fmax)	124 kN
MISCELLANEOUS	
Pattern (Schema)	B
PERFORMANCE RATINGS	
Rating Axial Static	1 890 kN Not simultaneous with other listed dynamic ratings
Rating Tilting Moment Static	276 kNm Not simultaneous with other listed dynamic ratings
Rating Tooth Force Normal	62 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Max	124 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	24 holes - 24; M18
Inner ring mounting	24 holes - 24; M18
GEAR INTERFACE	
Pitch system	module
Module reference	8 mm
Number of teeth	74
SOURCE TRACEABILITY	
Source document code	LA-LEONESSA-EXTERNAL-GEAR-CATALOG-2017
Source file	SLEWING-BEARINGS-WITH-EXTERNAL-GEAR.pdf
PDF page	4
Printed page	4
Source language	EN

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	la-leonessa-2se-static_load_curve.webp SHA-256: 0056d7fd4ded2922ffa0000f4b2784841e0dbba7de039b531b9334852625cba1
Outline Drawing	la-leonessa-2se-drawing.webp SHA-256: 9def12f376fbd9bc222f66ab0503412bd5a475fdfe624e4dbfe0ca549ea4d61f

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



la-leonessa-2se-static_load_curve.webp | SHA-256:
0056d7fd4ded2922ffa0000f4b2784841e0dbba7de039b531b9334852625cba1

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

VINQQWYSHNSJ36EL2NW65PYG6D

SOURCE FILE

**SLEWING-BEARINGS-WITH-EXTERNAL-GEAR.
pdf**

VERIFICATION

**Level 3 - MERYDOM Engineering
Verified**

SOURCE DOCUMENT

**LA-LEONESSA-EXTERNAL-GEAR-CATALOG-20
17**

SOURCE LOCATION

PDF page 4 | Printed page 4

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/la-leonessa/ve061b05/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.