

Factory-Verified Replacement

MERYDOM VE074Z100

Certified for interchange with La Leonessa VE074Z100. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

VE074Z100

SERIES

Z_EXTERNAL Series

OVERALL OD

742.8 mm

OVERALL HEIGHT

56 mm

REFERENCE

La Leonessa VE074Z100

STRUCTURE

Flanged Four Point Contact Ball


OVERALL ID

534 mm

GEAR

D tan di li

Published Technical Drawing



la-leonessa-z-external-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	VE074Z100
Certified interchangeable with	La Leonessa VE074Z100
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	4Q33HPPXS5JL7IDEOO7BD2YPKO
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	La Leonessa
Reference series	Z_EXTERNAL Series
Reference model	VE074Z100
Bearing structure	Flanged Four Point Contact Ball
Gear arrangement	D tan di li
DIMENSION	
Mass (P)	47 kg
Overall outside diameter (De)	742,8 mm
Overall inside diameter (Di)	534 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	56 mm
Dim Dr (Dr)	644 mm
MOUNTING	
Outer ring bolt circle (Ie)	685 mm
Outer ring mounting-hole count (ne)	16
Outer ring mounting-hole specification (Me)	M12
Inner ring bolt circle (Ii)	562 mm
Inner ring mounting-hole count (ni)	16
Inner ring mounting-hole specification (Mi)	M16
GEAR	
Gear module (m)	6 mm
Gear tooth count (z)	122
Liebherr catalogue gear dimension k*m (km)	0,6 mm
Gear pitch diameter (Dp)	732 mm
Gear Tooth Height (Hd)	45,5 mm
PERFORMANCE	
Basic static axial load rating (C0a)	410 kN
Static tilting moment rating (M0r)	59 kNm
Normal tooth force (Fnom)	14,2 kN
Maximum tooth force (Fmax)	28,4 kN

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE RATINGS	
Rating Axial Static	410 kN Not simultaneous with other listed dynamic ratings
Rating Tilting Moment Static	59 kNm Not simultaneous with other listed dynamic ratings
Rating Tooth Force Normal	14,2 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Max	28,4 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	16 holes - 16; M12
Inner ring mounting	16 holes - 16; M16
GEAR INTERFACE	
Pitch system	module
Module reference	6 mm
Number of teeth	122
SOURCE TRACEABILITY	
Source document code	LA-LEONESSA-FLANGED-SLEWING-BEARINGS-CATALOG-2013
Source file	Catalogo_flangiati.pdf
PDF page	2
Printed page	2
Source language	EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	la-leonessa-z-external-static_load_curve.webp SHA-256: 7e5942d2250300b774b9a47276b2238aec0fd1620da21ca6fa1266da04750467

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PUBLISHED TECHNICAL MEDIA (CONTINUED)	
Outline Drawing	la-leonessa-z-external-drawing.webp SHA-256: c45a0346554562dcd15b471c82ba9af10ca23e5d51261fd5da5782bda8f905b1

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



la-leonessa-z-external-static_load_curve.webp | SHA-256:
7e5942d2250300b774b9a47276b2238aec0fd1620da21ca6fa1266da04750467

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

4Q33HPPXS5JL7IDEOO7BD2YPKO

SOURCE FILE

Catalogo_flangiati.pdf

VERIFICATION

Level 3 - MERYDOM Engineering
Verified

SOURCE DOCUMENT

LA-LEONESSA-FLANGED-SLEWING-BEARINGS
-CATALOG-2013

SOURCE LOCATION

PDF page 2 | Printed page 2

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/la-leonessa/ve074z100/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.