

Factory-Verified Replacement

MERYDOM VE160B00

Certified for interchange with La Leonessa VE160B00. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

VE160B00

SERIES

2SE Series

OVERALL OD

1,604 mm

OVERALL HEIGHT

144 mm

REFERENCE

La Leonessa VE160B00

STRUCTURE

ift s ral bilyal rulman


OVERALL ID

1,208 mm

GEAR

D tan di li

Published Technical Drawing



la-leonessa-2se-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	VE160B00
Certified interchangeable with	La Leonessa VE160B00
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	GG6P2U7YMKZZLH223VJVHSYPH4
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	La Leonessa
Reference series	2SE Series
Reference model	VE160B00
Bearing structure	ift s ral bilyal rulman
Gear arrangement	D tan di li
DIMENSION	
Mass (P)	698 kg
Overall outside diameter (De)	1 604 mm
Overall inside diameter (Di)	1 208 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	144 mm
Dim Dr (Dr)	1 389,5 mm
MOUNTING	
Outer ring bolt circle (Ie)	1 500 mm
Outer ring mounting-hole count (ne)	48
Outer ring mounting-hole specification (Me)	M27
Inner ring bolt circle (Ii)	1 280 mm
Inner ring mounting-hole count (ni)	48
Inner ring mounting-hole specification (Mi)	M27
GEAR	
Gear module (m)	10 mm
Gear tooth count (z)	158
Addendum modification product x^*m (xm)	2,5 mm
Liebherr catalogue gear dimension k^*m (km)	0,5 mm
Gear pitch diameter (Dp)	1 585 mm
Gear Tooth Height (Hd)	90 mm
PERFORMANCE	
Basic static axial load rating (C0a)	7 930 kN
Static tilting moment rating (M0r)	2 500 kNm
Normal tooth force (Fnom)	103 kN

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE (CONTINUED)	
Maximum tooth force (Fmax)	206 kN
MISCELLANEOUS	
Pattern (Schema)	B
PERFORMANCE RATINGS	
Rating Axial Static	7 930 kN Not simultaneous with other listed dynamic ratings
Rating Tilting Moment Static	2 500 kNm Not simultaneous with other listed dynamic ratings
Rating Tooth Force Normal	103 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Max	206 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	48 holes - 48; M27
Inner ring mounting	48 holes - 48; M27
GEAR INTERFACE	
Pitch system	module
Module reference	10 mm
Number of teeth	158
SOURCE TRACEABILITY	
Source document code	LA-LEONESSA-EXTERNAL-GEAR-CATALOG-2017
Source file	SLEWING-BEARINGS-WITH-EXTERNAL-GEAR.pdf
PDF page	12
Printed page	12
Source language	EN


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	la-leonessa-2se-static_load_curve.webp SHA-256: 0056d7fd4ded2922ffa0000f4b2784841e0dbba7de039b531b9334852625cba1
Outline Drawing	la-leonessa-2se-drawing.webp SHA-256: 9def12f376fbd9bc222f66ab0503412bd5a475fdfe624e4dbfe0ca549ea4d61f

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



la-leonessa-2se-static_load_curve.webp | SHA-256:
0056d7fd4ded2922ffa0000f4b2784841e0dbba7de039b531b9334852625cba1

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

GG6P2U7YMKZZLH223VJVHSYPH4

SOURCE FILE

SLEWING-BEARINGS-WITH-EXTERNAL-GEAR.pdf

VERIFICATION

**Level 3 - MERYDOM Engineering
Verified**

SOURCE DOCUMENT

LA-LEONESSA-EXTERNAL-GEAR-CATALOG-2017

SOURCE LOCATION

PDF page 12 | Printed page 12

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/la-leonessa/ve160b00/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.