

Factory-Verified Replacement

MERYDOM VI040A01

Certified for interchange with La Leonessa VI040A01. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

VI040A01

SERIES

1SI Series

OVERALL OD

400 mm

OVERALL HEIGHT

55 mm

REFERENCE

La Leonessa VI040A01

STRUCTURE

D rt nokta temasl bilyal


OVERALL ID

216 mm

GEAR

ten di li

Published Technical Drawing



la-leonessa-1si-drawing.webp



Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	VI040A01
Certified interchangeable with	La Leonessa VI040A01
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	YJOPWKGKB2R6JHKRXXUTKCTBMF
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	La Leonessa
Reference series	1SI Series
Reference model	VI040A01
Bearing structure	D rt nokta temasl bilyal
Gear arrangement	ten di li
DIMENSION	
Mass (P)	25 kg
Overall outside diameter (De)	400 mm
Overall inside diameter (Di)	216 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	55 mm
Dim Dr (Dr)	310 mm
MOUNTING	
Outer ring bolt circle (Ie)	358 mm
Outer ring mounting-hole count (ne)	24
Outer ring mounting-hole specification (Me)	M14
Inner ring bolt circle (Ii)	259 mm
Inner ring mounting-hole count (ni)	16
Inner ring mounting-hole specification (Mi)	M14
GEAR	
Gear module (m)	4 mm
Gear tooth count (z)	56
Gear pitch diameter (Dp)	224 mm
Gear Tooth Height (Hd)	35 mm
PERFORMANCE	
Basic static axial load rating (C0a)	700 kN
Static tilting moment rating (M0r)	43 kNm
Normal tooth force (Fnom)	11 kN
Maximum tooth force (Fmax)	22 kN
MISCELLANEOUS	

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MISCELLANEOUS (CONTINUED)	
Pattern (Schema)	A
PERFORMANCE RATINGS	
Rating Axial Static	700 kN Not simultaneous with other listed dynamic ratings
Rating Tilting Moment Static	43 kNm Not simultaneous with other listed dynamic ratings
Rating Tooth Force Normal	11 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Max	22 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	24 holes - 24; M14
Inner ring mounting	16 holes - 16; M14
GEAR INTERFACE	
Pitch system	module
Module reference	4 mm
Number of teeth	56
SOURCE TRACEABILITY	
Source document code	LA-LEONESSA-INTERNAL-GEAR-CATALOG-2017
Source file	SLEWING-BEARINGS-WITH-INTERNAL-GEAR.pdf
PDF page	4
Printed page	4
Source language	EN
Original unit system	Metric

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	la-leonessa-1si-static_load_curve.webp SHA-256: 0b170a48507420b5ae37a22d4354cc69ba563923e9226723d7a4253fd72d5189
Outline Drawing	la-leonessa-1si-drawing.webp SHA-256: 3c0269351f1480df2b4130d7fb5c79552a0896a4f557467d7b138da54c54c490

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



la-leonessa-1si-static_load_curve.webp | SHA-256:
0b170a48507420b5ae37a22d4354cc69ba563923e9226723d7a4253fd72d5189

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

YJOPWKGKBB2R6JHKRXXUTKCTBMF

SOURCE FILE

**SLEWING-BEARINGS-WITH-INTERNAL-GEAR.
pdf**

VERIFICATION

**Level 3 - MERYDOM Engineering
Verified**

SOURCE DOCUMENT

**LA-LEONESSA-INTERNAL-GEAR-CATALOG-20
17**

SOURCE LOCATION

PDF page 4 | Printed page 4

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/la-leonessa/vi040a01/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.