

Factory-Verified Replacement

MERYDOM VI120B01

Certified for interchange with La Leonessa VI120B01. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

VI120B01

SERIES

2SI Series

OVERALL OD

1,200 mm

OVERALL HEIGHT

110 mm

REFERENCE

La Leonessa VI120B01

STRUCTURE

ift s ral bilyal rulman

OVERALL ID

963.5 mm

GEAR

ten di li

Published Technical Drawing



la-leonessa-2si-drawing.webp



Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| MERYDOM CERTIFIED PRODUCT            |                                        |
|--------------------------------------|----------------------------------------|
| Product brand                        | MERYDOM                                |
| MERYDOM model                        | VI120B01                               |
| Certified interchangeable with       | La Leonessa VI120B01                   |
| Verification status                  | Level 3 - MERYDOM Engineering Verified |
| Reviewed by                          | MERYDOM Engineering Department         |
| Public record UID                    | 7JYHXBVNXC4YAGTFEQW6EEKJGR             |
| MATERIALS                            |                                        |
| Configurable ring material options   | 42CrMo / 50Mn                          |
| Seal material                        | NBR - Nitrile rubber                   |
| Configurable spacer material options | Engineering nylon / Brass              |
| IDENTIFICATION                       |                                        |
| Reference brand                      | La Leonessa                            |
| Reference series                     | 2SI Series                             |
| Reference model                      | VI120B01                               |
| Bearing structure                    | ift s ral bilyal rulman                |
| Gear arrangement                     | ten di li                              |
| DIMENSION                            |                                        |
| Mass (P)                             | 247 kg                                 |
| Overall outside diameter (De)        | 1 200 mm                               |
| Overall inside diameter (Di)         | 963,5 mm                               |

## Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| DIMENSION (CONTINUED)                       |            |
|---------------------------------------------|------------|
| Overall height (H)                          | 110 mm     |
| Dim Dr (Dr)                                 | 1 102,5 mm |
| MOUNTING                                    |            |
| Outer ring bolt circle (Ie)                 | 1 160 mm   |
| Outer ring mounting-hole count (ne)         | 48         |
| Outer ring mounting-hole specification (Me) | M20        |
| Inner ring bolt circle (Ii)                 | 1 040 mm   |
| Inner ring mounting-hole count (ni)         | 48         |
| Inner ring mounting-hole specification (Mi) | M20        |
| GEAR                                        |            |
| Gear module (m)                             | 10 mm      |
| Gear tooth count (z)                        | 98         |
| Liebherr catalogue gear dimension k*m (km)  | 1,75 mm    |
| Gear pitch diameter (Dp)                    | 980 mm     |
| Gear Tooth Height (Hd)                      | 88 mm      |
| PERFORMANCE                                 |            |
| Basic static axial load rating (C0a)        | 4 210 kN   |
| Static tilting moment rating (M0r)          | 977 kNm    |
| Normal tooth force (Fnom)                   | 69 kN      |
| Maximum tooth force (Fmax)                  | 138 kN     |

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| MISCELLANEOUS                |                                                               |
|------------------------------|---------------------------------------------------------------|
| Pattern (Schema)             | B                                                             |
| PERFORMANCE RATINGS          |                                                               |
| Rating Axial Static          | 4 210 kN   Not simultaneous with other listed dynamic ratings |
| Rating Tilting Moment Static | 977 kNm   Not simultaneous with other listed dynamic ratings  |
| Rating Tooth Force Normal    | 69 kN   Not simultaneous with other listed dynamic ratings    |
| Rating Tooth Force Max       | 138 kN   Not simultaneous with other listed dynamic ratings   |
| MOUNTING INTERFACES          |                                                               |
| Outer ring mounting          | 48 holes - 48; M20                                            |
| Inner ring mounting          | 48 holes - 48; M20                                            |
| GEAR INTERFACE               |                                                               |
| Pitch system                 | module                                                        |
| Module reference             | 10 mm                                                         |
| Number of teeth              | 98                                                            |
| SOURCE TRACEABILITY          |                                                               |
| Source document code         | LA-LEONESSA-INTERNAL-GEAR-CATALOG-2017                        |
| Source file                  | SLEWING-BEARINGS-WITH-INTERNAL-GEAR.pdf                       |
| PDF page                     | 8                                                             |
| Printed page                 | 8                                                             |
| Source language              | EN                                                            |
| Original unit system         | Metric                                                        |

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| PUBLISHED TECHNICAL MEDIA |                                                                                                                       |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Load Curve Chart          | la-leonessa-2si-static_load_curve.webp   SHA-256:<br>2d07d5007c414f54f7e8476084d020a30af3af05a960e7f690827754e00574cb |
| Outline Drawing           | la-leonessa-2si-drawing.webp   SHA-256:<br>3c0269351f1480df2b4130d7fb5c79552a0896a4f557467d7b138da54c54c490           |

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



la-leonessa-2si-static\_load\_curve.webp | SHA-256:  
2d07d5007c414f54f7e8476084d020a30af3af05a960e7f690827754e00574cb

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

## Source and Verification Traceability

### PUBLIC RECORD UID

7JYHXBVNXC4YAGTFEQW6EEKJGR

### SOURCE FILE

**SLEWING-BEARINGS-WITH-INTERNAL-GEAR.  
pdf**

### VERIFICATION

**Level 3 - MERYDOM Engineering  
Verified**

### SOURCE DOCUMENT

**LA-LEONESSA-INTERNAL-GEAR-CATALOG-20  
17**

### SOURCE LOCATION

**PDF page 8 | Printed page 8**

### REVIEWED BY

**MERYDOM Engineering Department**

## Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

### Request Price, Delivery and Final Engineering Confirmation

Email: [jovi@merydom.com](mailto:jovi@merydom.com) | Email: [andi@merydom.com](mailto:andi@merydom.com) | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/la-leonessa/vi120b01/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.