

Factory-Verified Replacement

MERYDOM VI177B00

Certified for interchange with La Leonessa VI177B00. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

VI177B00

SERIES

2SI Series

OVERALL OD

1,770 mm

OVERALL HEIGHT

135 mm

REFERENCE

La Leonessa VI177B00

STRUCTURE

ift s ral bilyal rulman


OVERALL ID

1,375 mm


GEAR

ten di li

Published Technical Drawing



la-leonessa-2si-drawing.webp



Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	VI177B00
Certified interchangeable with	La Leonessa VI177B00
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	NYBI2RNH7UN2NHDQO52FECBRMR
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	La Leonessa
Reference series	2SI Series
Reference model	VI177B00
Bearing structure	ift s ral bilyal rulman
Gear arrangement	ten di li
DIMENSION	
Mass (P)	758 kg
Overall outside diameter (De)	1 770 mm
Overall inside diameter (Di)	1 375 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	135 mm
Dim Dr (Dr)	1 605,5 mm
Dim Centering External (Ce)	1.760 0/-0,5 mm
Dim Centering Internal (Ci)	1.580 0/-0,5 mm
MOUNTING	
Outer ring bolt circle (Ie)	1 710 mm
Outer ring mounting-hole count (ne)	48
Outer ring mounting-hole specification (Me)	M30
Inner ring bolt circle (Ii)	1 500 mm
Inner ring mounting-hole count (ni)	48
Inner ring mounting-hole specification (Mi)	M30
GEAR	
Gear module (m)	14 mm
Gear tooth count (z)	100
Liebherr catalogue gear dimension k*m (km)	1,5 mm
Gear pitch diameter (Dp)	1 400 mm
Gear Tooth Height (Hd)	115 mm
PERFORMANCE	
Basic static axial load rating (C0a)	9 280 kN
Static tilting moment rating (M0r)	3 542 kNm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE (CONTINUED)	
Normal tooth force (F _{nom})	185 kN
Maximum tooth force (F _{max})	370 kN
MISCELLANEOUS	
Pattern (Schema)	B
PERFORMANCE RATINGS	
Rating Axial Static	9 280 kN Not simultaneous with other listed dynamic ratings
Rating Tilting Moment Static	3 542 kNm Not simultaneous with other listed dynamic ratings
Rating Tooth Force Normal	185 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Max	370 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	48 holes - 48; M30
Inner ring mounting	48 holes - 48; M30
GEAR INTERFACE	
Pitch system	module
Module reference	14 mm
Number of teeth	100
SOURCE TRACEABILITY	
Source document code	LA-LEONESSA-INTERNAL-GEAR-CATALOG-2017
Source file	SLEWING-BEARINGS-WITH-INTERNAL-GEAR.pdf
PDF page	12
Printed page	12


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Source language	EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	la-leonessa-2si-static_load_curve.webp SHA-256: 2d07d5007c414f54f7e8476084d020a30af3af05a960e7f690827754e00574cb
Outline Drawing	la-leonessa-2si-drawing.webp SHA-256: 3c0269351f1480df2b4130d7fb5c79552a0896a4f557467d7b138da54c54c490

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



la-leonessa-2si-static_load_curve.webp | SHA-256:
2d07d5007c414f54f7e8476084d020a30af3af05a960e7f690827754e00574cb

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID NYBI2RNH7UN2NHDQO52FECBRMR	SOURCE DOCUMENT LA-LEONESSA-INTERNAL-GEAR-CATALOG-2017
SOURCE FILE SLEWING-BEARINGS-WITH-INTERNAL-GEAR.pdf	SOURCE LOCATION PDF page 12 Printed page 12
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/la-leonessa/vi177b00/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.