

Factory-Verified Replacement

MERYDOM KUD01750-035ZA15-900-000


Certified for interchange with Liebherr KUD01750-035ZA15-900-000. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL	REFERENCE
KUD01750-035ZA15-900-000	Liebherr KUD01750-035ZA15-900-000
SERIES	STRUCTURE
KUD_35_ZA Series	ift s ral bilyal rulman
OVERALL OD	OVERALL ID
1,985.2 mm	1,620 mm
OVERALL HEIGHT	GEAR
138 mm	D tan di li

Published Technical Drawing



liebherr-page-103-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	KUD01750-035ZA15-900-000
Certified interchangeable with	Liebherr KUD01750-035ZA15-900-000
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	EN22BMG4EUNUL7GFUMKLDF7PYK
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Liebherr
Reference series	KUD_35_ZA Series
Reference model	KUD01750-035ZA15-900-000
Bearing structure	ift s ral bilyal rulman
Gear arrangement	D tan di li
DIMENSION	
Mass (Weight)	789 kg
Overall outside diameter (Da)	1 985,2 mm
Overall inside diameter (Di)	1 620 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	138 mm
Liebherr catalogue dimension O (O)	1 784 mm
Liebherr catalogue dimension U (U)	1 779 mm
Liebherr catalogue dimension H1 (H1)	104 mm
Liebherr catalogue dimension H2 (H2)	132 mm
MOUNTING	
Outer ring bolt circle (La)	1 860 mm
Inner ring bolt circle (Li)	1 670 mm
La/Li mounting-hole count (n)	44
Mounting fastener specification (M)	24
Liebherr catalogue count n1 (n1)	3
GEAR	
Gear pitch diameter (d)	1 946 mm
Gear module (m)	14 mm
Gear tooth count (z)	139
Addendum modification product x^*m (x^*m)	7 mm
Liebherr catalogue gear dimension k^*m (k^*m)	-1,4 mm
Gear face width (b)	104 mm
PERFORMANCE	
Standard tooth force (Fz standard)	133,6 kN

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE (CONTINUED)	
Maximum tooth force (Fz maximum)	267,2 kN
Static load rating (Cstat)	12 022 kN
Dynamic load rating (Cdyn)	981 kN
PERFORMANCE RATINGS	
Rating Dynamic	981 kN Not simultaneous with other listed dynamic ratings
Rating Static	12 022 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Max	267,2 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Standard	133,6 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	44 holes - 24
Inner ring mounting	44 holes - 24
GEAR INTERFACE	
Pitch system	module
Module reference	14 mm
Number of teeth	139
SOURCE TRACEABILITY	
Source document code	LIEBHERR-SLEWING-BEARINGS-PRODUCT-CATALOGUE-2018
Source file	liebherr-slewing-bearings-product-catalogue-pt-metric-web.pdf
PDF page	103
Printed page	103


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Source language	EN
Original unit system	Mixed_metric_dp_threads
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	liebherr-page-103-curve.webp SHA-256: 98271b1d7b08f889bc64a242e0c33cb8d386a6b1032b854521922e2dca01ba61
Outline Drawing	liebherr-page-103-drawing.webp SHA-256: b3670e28f44718c17d910c2d4fe16000d18c7237d1a34056433475f67c42e9d1

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



liebherr-page-103-curve.webp | SHA-256: 98271b1d7b08f889bc64a242e0c33cb8d386a6b1032b854521922e2dca01ba61

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

EN22BMG4EUNUL7GFUMKLDF7PYK

SOURCE FILE

liebherr-slewing-bearings-product-ca
talogue-pt-metric-web.pdf

VERIFICATION

Level 3 - MERYDOM Engineering
Verified

SOURCE DOCUMENT

LIEBHERR-SLEWING-BEARINGS-PRODUCT-CA
TALOGUE-2018

SOURCE LOCATION

PDF page 103 | Printed page 103

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/liebherr/kud01750-035za15-900-000/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.