

Factory-Verified Replacement

MERYDOM KUD02100-040VO15-900-000


Certified for interchange with Liebherr KUD02100-040VO15-900-000. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL	REFERENCE
KUD02100-040VO15-900-000	Liebherr KUD02100-040VO15-900-000
SERIES	STRUCTURE
KUD_40_VO Series	D rt nokta temasl bilyal
OVERALL OD	OVERALL ID
2,245 mm	1,955 mm
OVERALL HEIGHT	GEAR
104 mm	Di lisiz

Published Technical Drawing



liebherr-page-096-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	KUD02100-040VO15-900-000
Certified interchangeable with	Liebherr KUD02100-040VO15-900-000
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	E6RFREKTI2SYOPNJD5LSZQOE5M
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Liebherr
Reference series	KUD_40_VO Series
Reference model	KUD02100-040VO15-900-000
Bearing structure	D rt nokta temasl bilyal
Gear arrangement	Di lisiz
DIMENSION	
Mass (Weight)	603 kg
Overall outside diameter (Da)	2 245 mm
Overall inside diameter (Di)	1 955 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	104 mm
Liebherr catalogue dimension O (O)	2 100 mm
Liebherr catalogue dimension U (U)	2 100 mm
Liebherr catalogue dimension H1 (H1)	92 mm
Liebherr catalogue dimension H2 (H2)	92 mm
MOUNTING	
Outer ring bolt circle (La)	2 185 mm
Inner ring bolt circle (Li)	2 015 mm
La/Li mounting-hole count (n)	60
Mounting fastener specification (M)	27
Liebherr catalogue count n1 (n1)	8
PERFORMANCE	
Static load rating (Cstat)	12 222 kN
Dynamic load rating (Cdyn)	986 kN
PERFORMANCE RATINGS	
Rating Dynamic	986 kN Not simultaneous with other listed dynamic ratings
Rating Static	12 222 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	60 holes - 27
Inner ring mounting	60 holes - 27


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

GEAR INTERFACE	
Integral gear	Not applicable - ungeared bearing
SOURCE TRACEABILITY	
Source document code	LIEBHERR-SLEWING-BEARINGS-PRODUCT-CATALOGUE-2018
Source file	liebherr-slewing-bearings-product-catalogue-pt-metric-web.pdf
PDF page	96
Printed page	96
Source language	EN
Original unit system	Mixed_metric_dp_threads
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	liebherr-page-096-curve.webp SHA-256: 4f26686c9d5bc6b26908f6a06409de21e4377262ab1f52b4f7ae9d348b42e664
Outline Drawing	liebherr-page-096-drawing.webp SHA-256: 25da85435c5b8f27bd6eaf320c6127ebc7c47c3a0deedc848b18ceaca59a4215

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



liebherr-page-096-curve.webp | SHA-256: 4f26686c9d5bc6b26908f6a06409de21e4377262ab1f52b4f7ae9d348b42e664

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID E6RFREKTI2SYOPNJD5LSZQOE5M	SOURCE DOCUMENT LIEBHERR-SLEWING-BEARINGS-PRODUCT-CA TALOGUE-2018
SOURCE FILE liebherr-slewing-bearings-product-ca talogue-pt-metric-web.pdf	SOURCE LOCATION PDF page 96 Printed page 96
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/liebherr/kud02100-040vo15-900-000/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.