

Factory-Verified Replacement

MERYDOM RKD04000-036ZA15-900-000

Certified for interchange with Liebherr RKD04000-036ZA15-900-000. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

RKD04000-036ZA15-900-000

REFERENCE

Liebherr RKD04000-036ZA15-900-000

SERIES

RKD_36_ZA Series

STRUCTURE

Makaral /bilyal kombinasyon

OVERALL OD

4,244 mm

OVERALL ID

3,792 mm


OVERALL HEIGHT

175 mm

GEAR

D tan di li

Published Technical Drawing



liebherr-page-149-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	RKD04000-036ZA15-900-000
Certified interchangeable with	Liebherr RKD04000-036ZA15-900-000
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	XFW7H5EDLUEEB5M5V7U6YIPG2P
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Liebherr
Reference series	RKD_36_ZA Series
Reference model	RKD04000-036ZA15-900-000
Bearing structure	Makara1 /bilya1 kombinasyon
Gear arrangement	D tan di li
DIMENSION	
Mass (Weight)	2 792 kg
Overall outside diameter (Da)	4 244 mm
Overall inside diameter (Di)	3 792 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	175 mm
Liebherr catalogue dimension O (O)	4 051 mm
Liebherr catalogue dimension U (U)	3 955 mm
Liebherr catalogue dimension H1 (H1)	125 mm
Liebherr catalogue dimension H2 (H2)	159 mm
MOUNTING	
Outer ring bolt circle (La)	4 095 mm
Inner ring bolt circle (Li)	3 858 mm
La/Li mounting-hole count (n)	76
Mounting fastener specification (M)	30
Liebherr catalogue count n1 (n1)	12
GEAR	
Gear pitch diameter (d)	4 176 mm
Gear module (m)	18 mm
Gear tooth count (z)	232
Addendum modification product x^*m (x^*m)	18 mm
Liebherr catalogue gear dimension k^*m (k^*m)	-1,8 mm
Gear face width (b)	125 mm
PERFORMANCE	
Standard tooth force (Fz standard)	195,6 kN

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE (CONTINUED)	
Maximum tooth force (Fz maximum)	391,2 kN
Static load rating (Cstat)	53 457 kN
Dynamic load rating (Cdyn)	4 830 kN
PERFORMANCE RATINGS	
Rating Dynamic	4 830 kN Not simultaneous with other listed dynamic ratings
Rating Static	53 457 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Max	391,2 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Standard	195,6 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	76 holes - 30
Inner ring mounting	76 holes - 30
GEAR INTERFACE	
Pitch system	module
Module reference	18 mm
Number of teeth	232
SOURCE TRACEABILITY	
Source document code	LIEBHERR-SLEWING-BEARINGS-PRODUCT-CATALOGUE-2018
Source file	liebherr-slewing-bearings-product-catalogue-pt-metric-web.pdf
PDF page	149
Printed page	149


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Source language	EN
Original unit system	Mixed_metric_dp_threads
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	liebherr-page-149-curve.webp SHA-256: 21834e3c088a66eab6ac08ec8ed6ab25b0e019220c4f16838f7d9e27eb7f8b28
Outline Drawing	liebherr-page-149-drawing.webp SHA-256: 513823a65f9a22dc3bfe4d3d82d3df300113aadb31ccefb6b25aada642508b87

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



liebherr-page-149-curve.webp | SHA-256: 21834e3c088a66eab6ac08ec8ed6ab25b0e019220c4f16838f7d9e27eb7f8b28

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID XFW7H5EDLUEEB5M5V7U6YIPG2P	SOURCE DOCUMENT LIEBHERR-SLEWING-BEARINGS-PRODUCT-CATALOGUE-2018
SOURCE FILE liebherr-slewing-bearings-product-catalogue-pt-metric-web.pdf	SOURCE LOCATION PDF page 149 Printed page 149
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/liebherr/rkd04000-036za15-900-000/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.