

Factory-Verified Replacement

MERYDOM ROD03150-032DA15-900-000

Certified for interchange with Liebherr ROD03150-032DA15-900-000. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

ROD03150-032DA15-900-000

REFERENCE

Liebherr ROD03150-032DA15-900-000

SERIES

ROD_32_DA Series

STRUCTURE

s ral makaral

OVERALL OD

3,476 mm

OVERALL ID

2,932 mm


OVERALL HEIGHT

181 mm

GEAR

D tan di li

Published Technical Drawing



liebherr-page-138-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	ROD03150-032DA15-900-000
Certified interchangeable with	Liebherr ROD03150-032DA15-900-000
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	PLNCH22C77CFEYUOV3J6BWNVGC
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Liebherr
Reference series	ROD_32_DA Series
Reference model	ROD03150-032DA15-900-000
Bearing structure	s ral makaral
Gear arrangement	D tan di li
DIMENSION	
Mass (Weight)	2 828 kg
Overall outside diameter (Da)	3 476 mm
Overall inside diameter (Di)	2 932 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	181 mm
Liebherr catalogue dimension O (O)	3 191 mm
Liebherr catalogue dimension U (U)	3 180 mm
Liebherr catalogue dimension H1 (H1)	139 mm
Liebherr catalogue dimension H2 (H2)	172 mm
MOUNTING	
Outer ring bolt circle (La)	3 305 mm
Inner ring bolt circle (Li)	3 010 mm
La/Li mounting-hole count (n)	56
Mounting fastener specification (M)	36
Liebherr catalogue count n1 (n1)	7
GEAR	
Gear pitch diameter (d)	3 420 mm
Gear module (m)	20 mm
Gear tooth count (z)	171
Addendum modification product x*m (x*m)	10 mm
Liebherr catalogue gear dimension k*m (k*m)	-2 mm
Gear face width (b)	139 mm
PERFORMANCE	
Standard tooth force (Fz standard)	241,7 kN

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE (CONTINUED)	
Maximum tooth force (Fz maximum)	483,4 kN
Static load rating (Cstat)	37 214 kN
Dynamic load rating (Cdyn)	3 627 kN
PERFORMANCE RATINGS	
Rating Dynamic	3 627 kN Not simultaneous with other listed dynamic ratings
Rating Static	37 214 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Max	483,4 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Standard	241,7 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	56 holes - 36
Inner ring mounting	56 holes - 36
GEAR INTERFACE	
Pitch system	module
Module reference	20 mm
Number of teeth	171
SOURCE TRACEABILITY	
Source document code	LIEBHERR-SLEWING-BEARINGS-PRODUCT-CATALOGUE-2018
Source file	liebherr-slewing-bearings-product-catalogue-pt-metric-web.pdf
PDF page	138
Printed page	138


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Source language	EN
Original unit system	Mixed_metric_dp_threads
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	liebherr-page-138-curve.webp SHA-256: b1622a13ed62b45e4a186e65029e20ac202b0e6214ef7e83f0da4d9920f107c1
Outline Drawing	liebherr-page-138-drawing.webp SHA-256: dce2e2500a3daa3838b8ca5cdd27994184301f3b96c333e0288bb3af5f2e59cb

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



liebherr-page-138-curve.webp | SHA-256: b1622a13ed62b45e4a186e65029e20ac202b0e6214ef7e83f0da4d9920f107c1

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID PLNCH22C77CFEYUOV3J6BWNVGC	SOURCE DOCUMENT LIEBHERR-SLEWING-BEARINGS-PRODUCT-CA TALOGUE-2018
SOURCE FILE liebherr-slewing-bearings-product-ca talogue-pt-metric-web.pdf	SOURCE LOCATION PDF page 138 Printed page 138
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/liebherr/rod03150-032da15-900-000/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.