

Factory-Verified Replacement

MERYDOM 16-1500-00

Certified for interchange with ROLLIX 16-1500-00. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

16-1500-00

REFERENCE

ROLLIX 16-1500-00

SERIES

16 Series

STRUCTURE

ift s ral    apraz makaral

OVERALL OD

1,747 mm

OVERALL ID

1,317 mm


OVERALL HEIGHT

150 mm

GEAR

D    tan di li

Published Technical Drawing



rollix-page-112-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| MERYDOM CERTIFIED PRODUCT            |                                        |
|--------------------------------------|----------------------------------------|
| Product brand                        | MERYDOM                                |
| MERYDOM model                        | 16-1500-00                             |
| Certified interchangeable with       | ROLLIX 16-1500-00                      |
| Verification status                  | Level 3 - MERYDOM Engineering Verified |
| Reviewed by                          | MERYDOM Engineering Department         |
| Public record UID                    | P2MFSMCLHW34XZOHLW2OGBWJX5             |
| MATERIALS                            |                                        |
| Configurable ring material options   | 42CrMo / 50Mn                          |
| Seal material                        | NBR - Nitrile rubber                   |
| Configurable spacer material options | Engineering nylon / Brass              |
| IDENTIFICATION                       |                                        |
| Reference brand                      | ROLLIX                                 |
| Reference series                     | 16 Series                              |
| Reference model                      | 16-1500-00                             |
| Bearing structure                    | ift s ral    apraz makaral             |
| Gear arrangement                     | D    tan di    li                      |
| DIMENSION                            |                                        |
| Overall height (HT)                  | 150 mm                                 |
| Overall outside diameter (Dia De)    | 1 747 mm                               |
| Outer ring height (He)               | 140 mm                                 |

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| DIMENSION (CONTINUED)                                |          |
|------------------------------------------------------|----------|
| Overall inside diameter (Dia Di)                     | 1 317 mm |
| Inner ring height (Hi)                               | 140 mm   |
| Assembly weight (Weight)                             | 929 kg   |
| MOUNTING                                             |          |
| Outer ring pilot diameter (Dia Ce)                   | 1 685 mm |
| Inner ring pilot diameter (Dia Ci)                   | 1 320 mm |
| Outer ring hole type (External ring hole type)       | Th       |
| Outer ring bolt circle (Dia Fe)                      | 1 606 mm |
| Outer ring mounting-hole count (Ne)                  | 60       |
| Outer ring mounting-hole specification (Dhe)         | 36 mm    |
| Inner ring hole type (Inner ring hole type)          | Th       |
| Inner ring bolt circle (Dia Fi)                      | 1 394 mm |
| Inner ring mounting-hole count (Ni)                  | 60       |
| Inner ring mounting-hole specification (Dhi)         | 36 mm    |
| GEAR                                                 |          |
| Gear module (Module)                                 | 14 mm    |
| Gear tooth count (Z)                                 | 122      |
| Gear face width (W)                                  | 130 mm   |
| PERFORMANCE                                          |          |
| Gear capacity, unhardened (Gear capacity unhardened) | 353 kN   |

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| PERFORMANCE (CONTINUED)                             |                                                             |
|-----------------------------------------------------|-------------------------------------------------------------|
| Gear capacity, hardened (Gear capacity hardened)    | 411 kN                                                      |
| MISCELLANEOUS                                       |                                                             |
| Ring with greasing holes (Ring with greasing holes) | I                                                           |
| Greasing hole type (Greasing hole type)             | R                                                           |
| PERFORMANCE RATINGS                                 |                                                             |
| Rating Gear Capacity Hardened                       | 411 kN   Not simultaneous with other listed dynamic ratings |
| Rating Gear Capacity Unhardened                     | 353 kN   Not simultaneous with other listed dynamic ratings |
| MOUNTING INTERFACES                                 |                                                             |
| Outer ring mounting                                 | 60 holes - External ring hole type Th; Dhe 36 mm            |
| Inner ring mounting                                 | 60 holes - Inner ring hole type Th; Dhi 36 mm               |
| GEAR INTERFACE                                      |                                                             |
| Pitch system                                        | module                                                      |
| Module reference                                    | 14 mm                                                       |
| Number of teeth                                     | 122                                                         |
| SOURCE TRACEABILITY                                 |                                                             |
| Source document code                                | ROLLIX-CATALOGUE-SLEWING-RINGS-2024-07                      |
| Source file                                         | ROLLIX.pdf                                                  |
| PDF page                                            | 112                                                         |
| Printed page                                        | 112                                                         |
| Source language                                     | EN                                                          |


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| SOURCE TRACEABILITY (CONTINUED) |                                                                                                             |
|---------------------------------|-------------------------------------------------------------------------------------------------------------|
| Original unit system            | Metric                                                                                                      |
| PUBLISHED TECHNICAL MEDIA       |                                                                                                             |
| Load Curve Chart                | rollix-page-112-curve.webp   SHA-256:<br>9ae717eb879e93936824607d3d9bc68e4fa1055aaed09024fe8cd15c67b2ce5d   |
| Outline Drawing                 | rollix-page-112-drawing.webp   SHA-256:<br>2102bcc75aee1dd325d53cdcc6ba5bc0e87e10022237a4ba706151ca65815e2b |

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



rollix-page-112-curve.webp | SHA-256: 9ae717eb879e93936824607d3d9bc68e4fa1055aaed09024fe8cd15c67b2ce5d

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

|                                                                               |                                                                              |
|-------------------------------------------------------------------------------|------------------------------------------------------------------------------|
| <div>PUBLIC RECORD UID</div> <div>P2MFSMCLHW34XZOHLW2OGBWJX5</div>            | <div>SOURCE DOCUMENT</div> <div>ROLLIX-CATALOGUE-SLEWING-RINGS-2024-07</div> |
| <div>SOURCE FILE</div> <div>ROLLIX.pdf</div>                                  | <div>SOURCE LOCATION</div> <div>PDF page 112   Printed page 112</div>        |
| <div>VERIFICATION</div> <div>Level 3 - MERYDOM Engineering<br/>Verified</div> | <div>REVIEWED BY</div> <div>MERYDOM Engineering Department</div>             |

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/rollix/16-1500-00/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.