

Factory-Verified Replacement

MERYDOM 061.20.0400.101.21.1503

Certified for interchange with Rothe Erde 061.20.0400.101.21.1503. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

**LEVEL 3 - MERYDOM ENGINEERING VERIFIED**

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

061.20.0400.101.21.1503

SERIES

06 Series

OVERALL OD

499.8 mm

OVERALL HEIGHT

55 mm

REFERENCE

Rothe Erde 061.20.0400.101.21.1503

STRUCTURE

Tek s ral d rt nokta temasl  
bilyal


OVERALL ID

325 mm

GEAR

D tan di li

Published Technical Drawing



page-074-outline.png

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| MERYDOM CERTIFIED PRODUCT            |                                        |
|--------------------------------------|----------------------------------------|
| Product brand                        | MERYDOM                                |
| MERYDOM model                        | 061.20.0400.101.21.1503                |
| Certified interchangeable with       | Rothe Erde 061.20.0400.101.21.1503     |
| Verification status                  | Level 3 - MERYDOM Engineering Verified |
| Reviewed by                          | MERYDOM Engineering Department         |
| Public record UID                    | SJU6X5Z5B2WZ7CDQBME6YTL6YH             |
| MATERIALS                            |                                        |
| Configurable ring material options   | 42CrMo / 50Mn                          |
| Seal material                        | NBR - Nitrile rubber                   |
| Configurable spacer material options | Engineering nylon / Brass              |
| IDENTIFICATION                       |                                        |
| Reference brand                      | Rothe Erde                             |
| Reference series                     | 06 Series                              |
| Reference model                      | 061.20.0400.101.21.1503                |
| Bearing structure                    | Tek s ral d rt nokta temasl bilyal     |
| Gear arrangement                     | D tan di li                            |
| DIMENSION                            |                                        |
| Raceway diameter (DL)                | 400 mm                                 |
| Overall outside diameter (Da)        | 499,8 mm                               |
| Overall inside diameter (Di)         | 325 mm                                 |

## Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| DIMENSION (CONTINUED)                     |         |
|-------------------------------------------|---------|
| Overall height (H)                        | 55 mm   |
| Catalog diameter O (O)                    | 401 mm  |
| Catalog diameter U (U)                    | 399 mm  |
| Ring height H1 (H1)                       | 46 mm   |
| Ring height H2 (H2)                       | 46 mm   |
| Lower ring offset Hu (Hu)                 | 9 mm    |
| Upper ring offset Ho (Ho)                 | 9 mm    |
| Assembly weight (Weight)                  | 35 kg   |
| MOUNTING                                  |         |
| Outer ring bolt circle (La)               | 448 mm  |
| Inner ring bolt circle (Li)               | 352 mm  |
| Common mounting-hole count (n)            | 16      |
| Common mounting-hole diameter (B)         | 13,5 mm |
| Metric bolt nominal size (M)              | 12 mm   |
| GEAR                                      |         |
| Gear pitch diameter (d)                   | 485 mm  |
| Gear module (m)                           | 5 mm    |
| Gear tooth count (z)                      | 97      |
| Profile shift product x m (x*m)           | 2,5 mm  |
| Tip-height modification product k m (k*m) | -0,5 mm |

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

|                                               |                                                               |
|-----------------------------------------------|---------------------------------------------------------------|
| GEAR (CONTINUED)                              |                                                               |
| Minimum gear face width (bmin)                | 45 mm                                                         |
| PERFORMANCE                                   |                                                               |
| Permitted circumferential force, normal (X1)  | 21,74 kN                                                      |
| Permitted circumferential force, maximum (X2) | 43,48 kN                                                      |
| MISCELLANEOUS                                 |                                                               |
| Grease nipple count (n1)                      | 2                                                             |
| PERFORMANCE RATINGS                           |                                                               |
| Catalog Reference X1                          | 21,74 kN   Not simultaneous with other listed dynamic ratings |
| Catalog Reference X2                          | 43,48 kN   Not simultaneous with other listed dynamic ratings |
| MOUNTING INTERFACES                           |                                                               |
| Outer ring mounting                           | 16 holes - M 12                                               |
| Inner ring mounting                           | 16 holes - B 13,5                                             |
| GEAR INTERFACE                                |                                                               |
| Pitch system                                  | module                                                        |
| Module reference                              | 5 mm                                                          |
| Number of teeth                               | 97                                                            |
| SOURCE TRACEABILITY                           |                                                               |
| Source document code                          | ROTHERDE_CATALOG_2023                                         |
| Source file                                   | Rothe Erde.pdf                                                |
| PDF page                                      | 74                                                            |
| Printed page                                  | 142-143                                                       |


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| SOURCE TRACEABILITY (CONTINUED) |                                                                                                         |
|---------------------------------|---------------------------------------------------------------------------------------------------------|
| Source language                 | EN                                                                                                      |
| Original unit system            | Metric                                                                                                  |
| PUBLISHED TECHNICAL MEDIA       |                                                                                                         |
| Load Curve Chart                | page-074-load-curves.png   SHA-256:<br>194de070d354539843844b18c12ac6e561fbf60097cd08c31ae76361dfdb759a |
| Outline Drawing                 | page-074-outline.png   SHA-256:<br>fbb761db55c943918e087e76a73723faa738c94b1e5085319051d15ed415de72     |

# Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



page-074-load-curves.png | SHA-256: 194de070d354539843844b18c12ac6e561fbf60097cd08c31ae76361dfdb759a

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

|                                                                               |                                                                          |
|-------------------------------------------------------------------------------|--------------------------------------------------------------------------|
| <div>PUBLIC RECORD UID</div> <div>SJU6X5Z5B2WZ7CDQBME6YTL6YH</div>            | <div>SOURCE DOCUMENT</div> <div>ROTHE_ERDE_CATALOG_2023</div>            |
| <div>SOURCE FILE</div> <div>Rothe Erde.pdf</div>                              | <div>SOURCE LOCATION</div> <div>PDF page 74   Printed page 142-143</div> |
| <div>VERIFICATION</div> <div>Level 3 - MERYDOM Engineering<br/>Verified</div> | <div>REVIEWED BY</div> <div>MERYDOM Engineering Department</div>         |

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/rothe-erde/061-20-0400-101-21-1503/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.