

Factory-Verified Replacement

MERYDOM RKS.060.25.1204

Certified for interchange with SKF RKS.060.25.1204. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

RKS.060.25.1204

REFERENCE

SKF RKS.060.25.1204

SERIES

SKF_BALL_MEDIUM_UNGEARED Series

STRUCTURE

D rt nokta temasl bilyal

OVERALL OD

1,289 mm

OVERALL ID

1,119 mm


OVERALL HEIGHT

mm

GEAR

Di lisiz

Published Technical Drawing



skf-p078-outline-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	RKS.060.25.1204
Certified interchangeable with	SKF RKS.060.25.1204
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	LXLS6PVLCERVID32HRIKLBj6F6
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	SKF
Reference series	SKF_BALL_MEDIUM_UNGEARED Series
Reference model	RKS.060.25.1204
Bearing structure	D rt nokta temasl bilyal
Gear arrangement	Di lisiz
DIMENSION	
Raceway diameter (dm)	1 204 mm
Overall outside diameter (D)	1 289 mm
SKF catalogue dimension D1 (D1)	1 207,5 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall inside diameter (d)	1 119 mm
SKF catalogue dimension d1 (d1)	1 200,5 mm
Mass (Mass)	120 kg
MOUNTING	
Outer ring bolt circle (Je)	1 mm
Outer ring mounting-hole specification (Ke)	25 716 mm
Outer ring mounting-hole count (Ne)	45 count
Inner ring bolt circle (Ji)	1 151 mm
Inner ring mounting-hole specification (Ki)	16 mm
Inner ring mounting-hole count (Ni)	45 count
PERFORMANCE	
Basic dynamic axial load rating (C)	508 kN
Basic static axial load rating (C0)	3 990 kN
PERFORMANCE RATINGS	
Basic Dynamic Axial	508 kN
Basic Static Axial	3 990 kN
MOUNTING INTERFACES	
Outer ring mounting	45 holes - 25716
Inner ring mounting	45 holes - 16
GEAR INTERFACE	


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

GEAR INTERFACE (CONTINUED)	
Integral gear	Not applicable - ungeared bearing
SOURCE TRACEABILITY	
Source document code	SKF_SLEWING_BEARINGS_PUB_BU_P2_06115_3_EN_2019_09
Source file	SKF_Slewing_Bearings_PUB_BU_P2_06115_3_EN_2019-09.pdf
PDF page	78
Printed page	78
Source language	EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	skf-p079-load-curve.webp SHA-256: d0750f686bf9acd3bb23fcb84f897d3bf90ae3d33818b05bdb04a93aab54a532
Outline Drawing	skf-p078-outline-drawing.webp SHA-256: 5ffbbfe7411e3b489abdc40ed10eee54cf4c20c070c948359c9c35be59eb38a7

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



skf-p079-load-curve.webp | SHA-256: d0750f686bf9acd3bb23fcb84f897d3bf90ae3d33818b05bdb04a93aab54a532

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

LXLS6PVLCEVID32HRIKLBJ6F6

SOURCE FILE

SKF_Slewing_Bearings_PUB_BU_P2_06115_3_EN_2019-09.pdf

VERIFICATION

**Level 3 - MERYDOM Engineering
Verified**

SOURCE DOCUMENT

SKF_SLEWING BEARINGS_PUB_BU_P2_06115_3_EN_2019_09

SOURCE LOCATION

PDF page 78 | Printed page 78

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/skf/rks-060-25-1204/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.