

Factory-Verified Replacement

MERYDOM RKS.062.20.0944

Certified for interchange with SKF RKS.062.20.0944. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

RKS.062.20.0944

REFERENCE

SKF RKS.062.20.0944

SERIES

SKF_BALL_MEDIUM_INTERNAL Series

STRUCTURE

D rt nokta temasl bilyal

OVERALL OD

1,016 mm

OVERALL ID

841.6 mm


OVERALL HEIGHT

mm

GEAR

ten di li

Published Technical Drawing



skf-p072-outline-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	RKS.062.20.0944
Certified interchangeable with	SKF RKS.062.20.0944
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	6IMCDZILB2LZXK4GBNSN7GFDID
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	SKF
Reference series	SKF_BALL_MEDIUM_INTERNAL Series
Reference model	RKS.062.20.0944
Bearing structure	D rt nokta temasl bilyal
Gear arrangement	ten di li
DIMENSION	
Raceway diameter (dm)	944 mm
Overall outside diameter (D)	1 016 mm
SKF catalogue dimension D1 (D1)	945,5 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall inside diameter (d)	841,6 mm
SKF catalogue dimension d1 (d1)	942,5 mm
Mass (Mass)	76 kg
MOUNTING	
Outer ring bolt circle (Je)	990 mm
Outer ring mounting-hole specification (Ke)	13,5 mm
Outer ring mounting-hole count (Ne)	44 count
Inner ring bolt circle (Ji)	905 mm
Inner ring mounting-hole specification (Ki)	M12 mm
Inner ring mounting-hole count (Ni)	44 count
PERFORMANCE	
Basic dynamic axial load rating (C)	286 kN
Basic static axial load rating (C0)	2 340 kN
PERFORMANCE RATINGS	
Basic Dynamic Axial	286 kN
Basic Static Axial	2 340 kN
MOUNTING INTERFACES	
Outer ring mounting	44 holes - 13,5
Inner ring mounting	44 holes - M12
GEAR INTERFACE	


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

GEAR INTERFACE (CONTINUED)	
Pitch system	Not published
SOURCE TRACEABILITY	
Source document code	SKF_SLEWING_BEARINGS_PUB_BU_P2_06115_3_EN_2019_09
Source file	SKF_Slewing_Bearings_PUB_BU_P2_06115_3_EN_2019-09.pdf
PDF page	72
Printed page	72
Source language	EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	skf-p073-load-curve.webp SHA-256: 4b36abe1a754a5f76d96560c758e4351c58d264a30309e79c771127b94e214de
Outline Drawing	skf-p072-outline-drawing.webp SHA-256: 830cadeb0c15d0e6c165a66426331190720ea875d6d356aa488ece826e52cbc1

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



skf-p073-load-curve.webp | SHA-256: 4b36abe1a754a5f76d96560c758e4351c58d264a30309e79c771127b94e214de

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID 6IMCDZILB2LZXK4GBNSN7GFDID	SOURCE DOCUMENT SKF_SLEWING BEARINGS_PUB_BU_P2_06115_3_EN_2019_09
SOURCE FILE SKF_Slewing_Bearings_PUB_BU_P2_06115_3_EN_2019-09.pdf	SOURCE LOCATION PDF page 72 Printed page 72
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/skf/rks-062-20-0944/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.