

Factory-Verified Replacement

MERYDOM I.1155.25.00.B

Certified for interchange with Torriani Gianni I.1155.25.00.B. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL
I.1155.25.00.B

REFERENCE
Torriani Gianni I.1155.25.00.B

SERIES
I_25_B Series

STRUCTURE
D rt nokta temasl bilyal


OVERALL OD
1,153 mm

OVERALL ID
910 mm

OVERALL HEIGHT
mm

GEAR
ten di li

Published Technical Drawing



i_25_b-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	I.1155.25.00.B
Certified interchangeable with	Torriani Gianni I.1155.25.00.B
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	7D7DQGQ52ZEDZXCJBJSIU44QSK
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Torriani Gianni
Reference series	I_25_B Series
Reference model	I.1155.25.00.B
Bearing structure	D rt nokta temasl bilyal
Gear arrangement	ten di li
DIMENSION	
Overall outside diameter (Da)	1 153 mm
Torriani catalogue dimension U (U)	1 056 mm
Torriani catalogue dimension C (C)	1 055 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall inside diameter (Di)	910 mm
Mass (Kg)	165 kg
MOUNTING	
Outer ring bolt circle (La)	1 115 mm
Outer ring mounting-hole count (na)	30
Inner ring bolt circle (Li)	994 mm
Inner ring mounting-hole count (ni)	30
GEAR	
Gear pitch diameter (P)	930 mm
Gear module (m)	10 mm
Gear tooth count (z)	93
PERFORMANCE	
Normal tooth force (Fz_normal)	42,1 kN
Maximum tooth force (Fz_max)	84,2 kN
PERFORMANCE RATINGS	
Rating Tooth Force Normal	42,1 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Max	84,2 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	30 holes -
Inner ring mounting	30 holes -


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

GEAR INTERFACE	
Pitch system	module
Module reference	10 mm
Number of teeth	93
SOURCE TRACEABILITY	
Source document code	TORRIANI_GIANNI_BALL_BEARINGS_CATALOG
Source file	catalogo-torriani-cuscinetti-a-sfere.pdf
PDF page	10
Printed page	10
Source language	IT-EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	i_25_b-static-load-curve.webp SHA-256: da63ccb22de3bec1381696743adcf346848cbe078c7e963798f5b9d922521b85
Outline Drawing	i_25_b-drawing.webp SHA-256: d4c75084b010060c9fc9a1ed0ff6279e7a25a9each164b843409bb17d00efe8c

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



i_25_b-static-load-curve.webp | SHA-256: da63ccb22de3bec1381696743adcf346848cbe078c7e963798f5b9d922521b85

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

7D7DQGQ52ZEDZXCJBJSIU44QSK

SOURCE FILE

catalogo-torriani-cuscinetti-a-sfere
.pdf

VERIFICATION

Level 3 - MERYDOM Engineering
Verified

SOURCE DOCUMENT

TORRIANI_GIANNI_BALL_BEARINGS_CATALOG

SOURCE LOCATION

PDF page 10 | Printed page 10

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/torriani-gianni/i-1155-25-00-b/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.