

Factory-Verified Replacement

MERYDOM I.1251.30.12.D.1-RV


Certified for interchange with Torriani Gianni I.1251.30.12.D.1-RV. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL	REFERENCE
I.1251.30.12.D.1-RV	Torriani Gianni I.1251.30.12.D.1-RV
SERIES	STRUCTURE
I_25_30_40_50_D_R Series	D rt nokta temasl bilyal
OVERALL OD	OVERALL ID
1,250 mm	979 mm
OVERALL HEIGHT	GEAR
91 mm	ten di li

Published Technical Drawing



i_25_30_40_50_d_r-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	I.1251.30.12.D.1-RV
Certified interchangeable with	Torriani Gianni I.1251.30.12.D.1-RV
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	FPI4FT6VXHNGHLEWCG7CNRINDD
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Torriani Gianni
Reference series	I_25_30_40_50_D_R Series
Reference model	I.1251.30.12.D.1-RV
Bearing structure	D rt nokta temasl bilyal
Gear arrangement	ten di li
DIMENSION	
Overall outside diameter (Da)	1 250 mm
Torriani catalogue dimension U (U)	1 142 mm
Overall inside diameter (Di)	979 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Torriani catalogue dimension Ha (Ha)	75 mm
Torriani catalogue dimension Hb (Hb)	75 mm
Overall height (H)	91 mm
Mass (Kg)	240 kg
MOUNTING	
Outer ring bolt circle (La)	1 212 mm
Outer ring mounting-hole count (na)	SC
Outer ring mounting-hole specification (da)	22 mm
Inner ring bolt circle (Li)	1 068 mm
Inner ring mounting-hole count (ni)	36
Inner ring mounting-hole specification (di)	22 mm
GEAR	
Gear pitch diameter (P)	990 mm
Gear module (m)	10 mm
Gear tooth count (z)	99
PERFORMANCE	
Normal tooth force (Fz_normal)	58 kN
Maximum tooth force (Fz_max)	116 kN
PERFORMANCE RATINGS	
Rating Tooth Force Normal	58 kN Not simultaneous with other listed dynamic ratings


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE RATINGS (CONTINUED)	
Rating Tooth Force Max	116 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	holes - da 22 mm
Inner ring mounting	36 holes - di 22 mm
GEAR INTERFACE	
Pitch system	module
Module reference	10 mm
Number of teeth	99
SOURCE TRACEABILITY	
Source document code	TORRIANI_GIANNI_BALL_BEARINGS_CATALOG
Source file	catalogo-torriani-cuscinetti-a-sfere.pdf
PDF page	17
Printed page	17
Source language	IT-EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	i_25_30_40_50_d_r-static-load-curve.webp SHA-256: 66b906cb4198099bfb534842664bb40fee555f3fe57d77dac389594e92c472fc
Outline Drawing	i_25_30_40_50_d_r-drawing.webp SHA-256: 36467aaddab979d0f7c3d120cef188a0a9f16153afd23a8244155cd45881c50e

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



i_25_30_40_50_d_r-static-load-curve.webp | SHA-256:
66b906cb4198099bfb534842664bb40fee555f3fe57d77dac389594e92c472fc

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

FPI4FT6VXHNGHLEWCG7CNRINDD

SOURCE FILE

**catalogo-torriani-cuscinetti-a-sfere
.pdf**

VERIFICATION

**Level 3 - MERYDOM Engineering
Verified**

SOURCE DOCUMENT

TORRIANI_GIANNI_BALL_BEARINGS_CATALOG

SOURCE LOCATION

PDF page 17 | Printed page 17

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/tr/urunler/muadil-doner-tabla-rulmanlari/torriani-gianni/i-1251-30-12-d-1-rv/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.