

Technical drawing of a mechanical assembly in cross-section. The drawing shows a central circular component with a cross-hatched pattern, surrounded by various housing and mounting parts. Dimensions are indicated with arrows and text. Key dimensions include:

- Overall width: $\text{Ø}187$
- Mounting hole: $\text{Ø}154 \cdot 16 \times \text{M}10$
- Central hole: $\text{Ø}135^{+0,2}$
- Mounting hole: $\text{Ø}136 \pm 0,5$
- Outer diameter: $\text{Ø}238_{-0,07}$
- Mounting hole: $\text{Ø}222 \cdot 16 \times \text{M}10$
- Outer diameter: $\text{Ø}189$
- Mounting hole: $\text{Ø}248 \cdot \text{m}4 \cdot \text{z}62$
- Overall width: $\text{Ø}259,36$

Other dimensions and features include:

- 35, 30, 4, $x \cdot m = 2$, M10, 10, 20, and 132 297.
- Central circular component with a cross-hatched pattern.
- Various housing and mounting parts.

VA 140188 V

The graph shows the relationship between the equivalent static tilting moment load (M_{oq}) and the horizontal load (F). The y-axis represents M_{oq} in kNm, ranging from 0 to 60. The x-axis represents F in kN, ranging from 0 to 1000. The curve starts at $M_{oq} = 10$ kNm when $F = 0$ kN and increases linearly to $M_{oq} = 20$ kNm when $F = 400$ kN.

kN	Equivalent static tilting moment load M_{oq} (kNm)
0	17.5
50	17.5
400	0

Seguire le indicazioni tecniche del catalogo originale.

INA VA 140188 V — Disegno CAD (PDF) | MERYDOM

mm · NTS · REV 1.0 · Foglio 1/1